ML9 S4FE LOCKER

Spec Sheet

Version	**V2.0**
Date	1/4/2023
Author	Thomas Van Hoofstadt



Cabinet dimensions:		
Width (total):	373	mm
Width (installed)	362	mm
Depth:	772	mm
Height*:	2014	mm
		*without feet installed
Weight:	120	kg
Lockers (Qty.):	9	lockers

Locker dimensions (inside clearance):		
Width (total):	300	mm
Width (net):	282	mm
Depth:	600	mm
Height*:	175	mm
		*net with smoke detector in the back: 133mm

Power supply (per locker):			
USB A/C	5VDC	3A max	15W
US net	110VAC	1,75A max	136,5 W
EU net	240VAC	1,75A max	297,5W

Electrical connection (per cabinet)		
Fuse 16A	Inside:	Diff 300mA
	Outside:	Diff 30mA
Power consumption (stand by):		100W

Components (per cabinet)		
Locks:	Electronic, single action with status feedback	
Fire Control PC:	EN54-7 & EN12094-1	
Fire detection:	2 zones (4 + 5x optical sensor) - 9 in total	
	EN54-7 & EN12094-1	
Fire resistance:	K21045 acoording to EN16763 (KiWa certified)	
Fire containment:	**30'HD - 30min***	**60' - 60min***
	*conditions:	
	- all locker doors must be closed at all times	
	- installtion by certified personnel	
	- max batt. capacity: 9 x 1100Wh total (multiple batteries per locker)	- max batt. capacity: 9 x 1100Wh (1 battery per locker)
	Aerosol, 2 stages (200 + 100g). 12 minute interval	Aerosol, 1 stages (200 g)
Fire Control:	K23001	
Fire Class:	A, B, C, F	
Power back-up:	12h total:	11,5h stand-by
		0,5h alarm